



# EVO-STIK Coving & Ceiling Tile Adhesive

A READY MIXED SOLVENT-FREE ADHESIVE

Date: 30 September 2019

Fact Sheet No.: TDS00274

## YOUR SMART ADVANTAGES

- For paper wrapped or polystyrene coving, polystyrene tiles, plaster & decorative plaster mouldings e.g. ceiling roses
- Easy to apply formulation
- High initial grab & permanent bond

## USES

EVO-STIK Coving & Ceiling Tile Adhesive is ready to use and will bond, in dry areas to sound surfaces. It is suitable for use with all types of paper wrapped and polystyrene coving, polystyrene tiles, plaster, and decorative plaster mouldings. EVO-STIK Coving & Ceiling Tile Adhesive has excellent initial grab and creates a permanent bond, making it ideal for quick repair jobs or speedy installation of entire projects.

## PRODUCT CHARACTERISTICS

|                  |                         |
|------------------|-------------------------|
| Colour           | Buff                    |
| Form             | Thixotropic paste       |
| Specific Gravity | 1.62 approx.            |
| Composition      | Filled acrylic emulsion |
| Product Code     | 30811671 2.5 L x1       |

## Storage/Shelf Life

Store for up to 24 months from date of manufacture when stored in original, unopened packaging under cool, dry conditions within the temperature range +5°C to +30°C and out of direct sunlight. Protect from frost.

## TYPICAL PERFORMANCE DATA (Approx.)

### Application Temperature

+5°C to +30°C

### Coverage

| Smooth Surface:                  | Rough Surface:                    |
|----------------------------------|-----------------------------------|
| Approx. area of 10m <sup>2</sup> | Approx. area of 5.5m <sup>2</sup> |
| 35m of Coving and Dado           | 15m of Coving and Dado            |
| 20 Ceiling roses                 | 10 Ceiling roses                  |

### Drying Times

Fixing tiles: Bonds permanently in 24 hours.  
 Mouldings: Allow 24 hours before decorating.  
 Coving & Dado rails: Remove location pins after 24 hours.  
 Note: Drying times may be affected by ambient conditions.

### Open Time

30 minutes at 20°C, 50% RH

### Solvent for Cleaning Up

Water

## DIRECTIONS FOR USE

IMPORTANT: Before using EVO-STIK Coving & Ceiling Tile Adhesive, refer to the relevant Health & Safety Data Sheet, available at [www.bostik.com/uk](http://www.bostik.com/uk).

## PREPARATION

1. Surfaces must be rigid, dry, flat, clean and free from dust and loose material. For best results, a good, firm surface is essential.
2. The surface that the coving is being applied to must be porous.

## APPLICATION

### Bonding Tiles & Moulding:

3. Spread adhesive to a maximum depth of 3mm over the back of tile or moulding using the notched spreader supplied.
4. Press firmly in place to ensure complete contact between adhesive and both surfaces. To avoid damage to face of tiles use a piece of card when positioning.
5. Allow 24 hours drying time before decorating mouldings.
6. Whilst wet, remove excess adhesive with a damp cloth.
7. Heavy mouldings made of plaster, bonded to a ceiling (e.g. ceiling roses) should also be mechanically fixed, as their weight may be too great for EVO-STIK Coving & Ceiling Tile Adhesive to hold.

### Coving & Dado Rails:

8. Spread adhesive onto coving or dado surface using a notched spreader.
9. Press firmly into position. Insert location pins into wall or both wall and ceiling to support while the adhesive dries. Remove after at least 24 hours.
10. Finally fill along upper and lower edges of coving to provide a smooth finish.

## CLEANING

11. Wet adhesive may be removed by; first carefully scraping away the excess and then using a water-moistened cloth to remove the wet film.
12. Dry adhesive can only be removed mechanically. Dampening it where possible can make removal a little easier.

## PRECAUTIONS IN USE

EVO-STIK Coving & Ceiling Tile Adhesive 'sets' by evaporation of water. Excess adhesive and non-porous surfaces will greatly extend the drying time.

For any application not covered please contact Technical Services on +44 (0) 1785 272625 or visit [www.bostik.com/uk](http://www.bostik.com/uk) for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for EVO-STIK Coving & Ceiling Tile Adhesive, available at [www.bostik.com/uk](http://www.bostik.com/uk).

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

|                    |                    |                   |  |
|--------------------|--------------------|-------------------|--|
| Sales              | Tel: 0844 371 1192 | Fax: 01785 241818 | <a href="mailto:customer.service@bostik.com">customer.service@bostik.com</a>   |
| Technical Advice   | Tel: 0844 371 1197 | Fax: 01785 272867 | <a href="mailto:technical.service@bostik.com">technical.service@bostik.com</a> |
| Safety Data Sheets | Tel: 01785 272625  | Fax: 01785 212962 | <a href="mailto:sds.box-eu@bostik.com">sds.box-eu@bostik.com</a>               |