



EVO-STIK Impact Solvent Free

WATER-BASED CONTACT ADHESIVE

Date: 20 July 2018

Fact Sheet No.: TDS00027

YOUR SMART ADVANTAGES

- High strength and bonds instantly on contact
- Safe clean and easy to use
- No need for clamping or support whilst the adhesive sets

USES

EVO-STIK Impact Solvent Free is a non-flammable polychloroprene rubber latex based adhesive which changes from white to translucent when dry. It is economical in use and gives excellent bond strength.

It is ideal for bonding most types of materials: wood, MDF, laminate, metal, rigid PVC, cork, leather, rubber, polystyrene, glass, mirror, stone and ceramics. It is also very suitable for bonding smooth porous surfaces of concrete or plaster as well as canvas and expanded polystyrene. Non-porous materials such as metals and painted surfaces may be bonded, provided that the adhesive films are allowed to dry completely before the bond is made.

PRODUCT CHARACTERISTICS

Colour	White (translucent when dry).
Form	Mobile aqueous emulsion
Specific Gravity	1.12 approx.
Composition	Polychloroprene latex/resin blend
Solids Content	Approx. 55%
Solvent	Water

Product Code	30812362 250ml Tins x 6
Storage/Shelf Life	Store for up to 12 months from date of manufacture when stored in original, unopened packaging under dry conditions within the temperature range of +5°C to +30°C.

TYPICAL PERFORMANCE DATA (Approx.)

Coverage	12m ² per litre single coat
	6m ² per litre single coat 2 surfaces
	3m ² per 250ml – 1 surface
	1.5m ² per 250ml – 2 surfaces

DIRECTIONS FOR USE

IMPORTANT: Before using EVO-STIK Impact Solvent Free refer to the relevant Health & Safety Data Sheet, available at www.bostik.co.uk.

PREPARATION

1. Substrates to be bonded must be perfectly clean dry and free from dust, paint, grease and loose material.
2. Smooth or polished surfaces must first be roughened with fine abrasive.
3. Rubber and similar materials must be abraded well and then the bonding area vigorously wiped with a cloth damped with EVO-STIK Adhesive Cleaner (a solvent based cleaner). Without such treatment a poor bond will result.
4. If degreasing is necessary, use EVO-STIK Adhesive Cleaner.

APPLICATION

5. To prevent splashes, place the tin on a flat surface and lever the lid off gently with a screwdriver.
6. EVO-STIK Impact Solvent Free is suitable for application by brush, paint pad, paint roller or sponge.

7. The use of a notched or serrated spreader is not recommended as too much adhesive will be applied and this will take very much longer to dry.
8. Thoroughly stir the contents of the container before use.
9. Application by paint pad or by roller is very quick and applies a smooth thin layer of adhesive which will dry reasonably quickly.
10. Both surfaces to be bonded should be coated with an even coat of adhesive and allowed to become touch dry.
11. Porous surfaces such as plaster may require a second coat. The milky white opaque adhesive becomes nearly clear when dry.
12. The adhesive dries by evaporation of water into the atmosphere and on porous substrates also by absorption of the water into the pores.
13. The drying time is very dependent on substrate, coating weight, temperature and humidity. Under normal conditions the film dries in 30 minutes at 20°C.
14. The process can be accelerated by warming e.g. by radiant heat or by passage of a current of warm air over the surface.

BONDING

15. It is important to leave the adhesive until it changes colour before bonding.
16. Align the surfaces carefully when in place; press together gently, preferably, within 2 hours of drying.
17. Apply as much pressure as possible by hand roller, static press or nip roller without causing damage. Sustained pressure is unnecessary.

CLEANING

18. Use a moist cloth to remove uncured product.
19. Cured product requires mechanical removal.

PRECAUTIONS IN USE

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.co.uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for EVO-STIK Impact Solvent Free, available at www.bostik.co.uk.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	Fax: 01785 212962	sds.box-eu@bostik.com